



SCANNER ONE 8 Ray



Light Source: Visible Laser Diode 650nm

Scan Pattern: Single Scan & Manual

Working Frequency: 433 MHz frequency

Communication Distance: Up to 300m at open places

Scan Precision: 3mil

Scan Rate: 300 times/second

Scan Width: 30mm@scan window, 220mm@200m

Depth of Scan Field: 0-280mm(0.33mm pcs0.9)

Scan Angle: 30° & 65° & 55° **Communication Distance:** 300m

Print Contrast: 10% UPC/EAN 100%

Interface: USB

Decoding Capability: UPC-A; UPC-E; EAN-8; EAN-13; Code39; Codabar; Code128; Interleaved 2 of 5; Industrial 2 of 5; Matrix 2 of 5; Code 93; UCC/EAN 128; MSI; UK/Plessey; ISBN/ISSN; GS1 Databar Expanded; GS1 Databar; GS1 Databar Limited, etc.

Size: L x W x H:170mm x 71mm

Charge Mode: Wired Charging

Weight: 180g

Material: ABS+PC

Voltage: 2200 mAh/DC 5V

Operating Current: 110mA/35mA

EMC: CE & FCC DOC compliance

IP Standard: IP54

Decoding Capability: all 1D barcode Including GS1 Humidity: 5% to 95% relative humidity

Shock: 1.5M drops

